
Chevron Walk Off Matting

General Information

A walk-off mat with a durable herringbone pattern offers non-directional scraping action. This product must be used for interior applications only and be installed by professional installers that have sufficient professional liability insurance coverage (aka Errors and Omissions Insurance) for the project. Caution should be used in the moving and lifting. Allow for appropriate equipment and manpower to safely move materials. Work safe and always follow the relevant safety procedures.

Matter Surfaces recommends installing and maintaining entrance matting at all outdoor entrances; this will improve air quality, reduce maintenance costs, and lengthen the life of your floors.

Proper glides must be used on all furniture that may slide directly across the floor, consult the furniture manufacturer for recommendations for use on resilient flooring. Heavy objects must not be moved directly across the floor; use protective boards.

Direct sunlight can cause UV damage (fading or bleaching) to most interior finishes, so Low E glass should be selected that will reduce the UV transmission to less than 1%. If not, applying 3M™ protection film (or similar) on the windows is recommended.

Do not install any material that has visible defects or damage. A contractor that installs any material that has visible defects or damage assumes responsibility for the damaged material.

Technical Data

Material	18 oz / yard ² , UV stabilized polypropylene & polyester yarn fibers
Backing	Heavy weight non-staining vinyl
Colors	Charcoal, chocolate, denim
Total Height	3/8"
Dimensions	2' x 3'; 3' x 4', 3' x 5'. 3' x 6', 4' x 10', 4' x 6', 4' x 8'
Roll Width	3', 4', 6'
Roll Length	60'
Border Width	1"
Limited Warranty	(1) year Commercial